

EST. 2023



SHIV SHAKTI INDUSTRIES
STRONG BOND. PERFECT FINISH.

STRONG BOND. PERFECT FINISH.

Complete Tile Installation Solutions
for Every Surface.

"Building Trust, One Bond at a Time"

Panipat, Haryana | Pan-India Supply

TRUSTED
QUALITY
FOR LASTING
PERFORMANCE



HIGH STRENGTH
Superior
bond & durability



**WATER & CHEMICAL
RESISTANT**
For long lasting
performance



FOR ALL TILE TYPES
Ceramic, vitrified,
porcelain & more



INTERIOR & EXTERIOR
Suitable for walls,
floors & wet areas



EASY TO USE
Smooth application
& excellent workability



HOW TO USE SSI TILE ADHESIVE & EPOXY GROUT

01



SURFACE PREPARATION
Ensure surface is clean, dry,
dust-free and structurally
sound.

02



MIXING THE ADHESIVE
Add powder to clean water
at recommended ratio.
Mix with a slow-speed
drill until smooth.

03



APPLYING THE ADHESIVE
Spread adhesive with a
notched trowel.
Press the tile firmly.

04



SETTING THE TILE
Adjust & fix the tile.
Ensure proper alignment
and even coverage.

05



GROUTING
After 24 hours,
apply grout using
a rubber float.
Clean excess with
a damp sponge.

3+
YEARS
EXPERIENCE

500+
HAPPY
CLIENTS

ISI
CERTIFIED

4
PRO
BRANDS

PAN-INDIA
SUPPLY

PRODUCT CATALOG 2026

INDIA'S TRUSTED TILE ADHESIVE MANUFACTURER

ISI CERTIFIED

SINCE 2023



ISI 9001:2015



BIS Compliant



Low VOC



EN 12004



Pan-India

BUILT ON
QUALITY.
DRIVEN BY
GROWING with TRUST.



SAFE & ECO FRIENDLY

Low VOC, safe for
environment and health.

EST. 2023

SHIV SHAKTI INDUSTRIES

Strong Bond · Lasting Trust

"Building Trust, One Bond at a Time"

Panipat, Haryana · Pan-India Supply

3+

Years Strong

500+

Happy Clients

ISI

Certified

4

Pro Brands

APPLICATIONS

Floor Tiling

Wall Cladding

Swimming Pools

Bathrooms

Heated Floors

Overlaying

Industrial



SHIV SHAKTI INDUSTRIES

QUALITY YOU CAN BUILD ON, TRUST YOU CAN RELY ON

3 YEARS
OF EXPERIENCE

Delivering high quality and reliable solutions for modern construction needs.



OUR PRODUCT RANGE



TILE ADHESIVE

High performance tile adhesives designed for strong bond, durability and long-lasting results on all types of surfaces.



EPOXY

Premium epoxy solutions for tile grouting and installations offering excellent strength, chemical resistance and superior finish.



CONSTRUCTION CHEMICAL

Advanced construction chemicals that enhance performance, improve durability and ensure long-term protection.



STRONG BOND



HIGH DURABILITY



WATER & CHEMICAL RESISTANT



ADVANCED TECHNOLOGY

BUILDING STRONGER SPACES, TOGETHER.

Corvell
— TILE ADHESIVE —

NEXITONE
CERAMIC

SSi
BUILD STRONG FOR EVER

STRONG BOND. BEAUTIFUL SPACES.

Premium Tile Adhesives for Every Need

Better Adhesion · Long Lasting · Superior Performance

"The right adhesive makes all the difference!"



STRONG ADHESION



DURABLE & LONG LASTING



WATER & WEATHER RESISTANT



FOR ALL TYPES OF TILES



IDEAL FOR FLOOR & WALL



CORVELL DIAMOND
Interior Floor & Wall



SSI SILVA BIO
Floor & Wall



NEXITONE SILVER
Tile Adhesive



SSI ELASTICA GEL S1
Floor & Wall



NEXITONE DIAMOND
Tile Adhesive



HIGH BOND STRENGTH
For Long Lasting Performance



EXCELLENT WORKABILITY
Easy to Apply



NO SHRINKAGE
Crack Free Finish



TRUSTED BY PROFESSIONALS
Preferred for Perfection

STRONG BOND. BEAUTIFUL SPACES. BUILT TO LAST.

ISI 9001:2015

BIS Compliant

Low VOC

EN 12004

Pan-India

INDIA'S TRUSTED TILE ADHESIVE MANUFACTURER · ISI CERTIFIED · SINCE 2023

COMPANY OVERVIEW

Who We Are · Vision & Mission · Core Values · Brands · Certifications
Product Catalog 2025 · Shiv Shakti Industries, Panipat, Haryana



ABOUT SHIV SHAKTI INDUSTRIES

Shiv Shakti Industries is India's trusted manufacturer of high-performance tile adhesives, epoxy grouts and waterproofing solutions, headquartered at HSIIDC Industrial Area, Panipat, Haryana. Founded in 2023 and ISI-certified, we proudly serve 500+ clients, contractors and architects across India through four professional brands:
SSI · NEXITONE · CORVELL · ORION

KEY PERFORMANCE INDICATORS

3+ Yrs

In Business

500+

Happy Clients

4

Pro Brands

ISI

BIS Certified

100%

Pan-India

OUR VISION

To be India's most trusted construction chemical brand — driving quality, innovation and sustainable growth across every corner of the nation.
Market Leader · National Reach · Quality Focus

OUR MISSION

Manufacturing superior-performance tile adhesives, grouts and waterproofing solutions that empower builders and exceed international quality standards.
R&D Driven · Reliable Supply · Builder Empowerment

OUR VALUES

Quality First · Integrity Always · Innovation Driven · Customer Obsessed · Sustainability Committed · Nationwide Reach
Sustainable · Trusted Partner · Award-Worthy

CERTIFICATIONS & COMPLIANCE STANDARDS

✓ ISI 9001:2015

✓ BIS Compliant

✓ Low VOC Formula

✓ EN 12004

✓ In-House Lab-Soon

✓ Pan-India Supply

OUR 4 PROFESSIONAL BRANDS

SSI

The Bond Professionals Trust

NEXITONE

Next-Level Tile Bonding

CORVELL

Advanced Bonding Technology

ORION

Industrial Strength Solutions

Manufacturing

HSIIDC, Panipat, Haryana

Testing Lab-Soon

In-House R&D Facility

Distribution

Pan-India Network

Standard

ISI / MSME / EN 12004

WHY CHOOSE SHIV SHAKTI INDUSTRIES?

ISI Certified

Quality assured by Bureau of Indian Standards.

MSME & EN 12004

Indian and European international standards.

Soon-In-House Lab

Every batch tested for bond strength & quality.

Low VOC Formula

Eco-conscious — healthier indoor air quality.

Pan-India Supply Soon

Covering all 28 states with reliable delivery.

5,00+ Clients

Trusted by builders and architects nationwide.

PRODUCT APPLICATION AREAS

Residential Flooring

Floor & wall tile fixing

Heated Floors

Thermally stable adhesive

Commercial Spaces

Shopping malls & offices

Industrial

Chemical-resistant epoxy

Swimming Pools

Waterproof epoxy systems

Hospitals

Hygienic sterile grouts

Bathrooms

Water-resistant adhesives

Overlaying

Re-tile without removal

OUR STORY

Shiv Shakti Industries was born in 2023 from a singular vision: to manufacture world-class tile adhesives and construction chemicals right here in India — at HSIIDC Industrial Area, Samalkha, Panipat, Haryana. Founded by a team of experienced construction professionals, we recognized a growing need in India for affordable yet premium-quality tile bonding solutions that could rival international brands. In just two years we grew from a single production line to a multi-brand operation serving 5,00+ builders, contractors, architects and developers across all major Indian cities and states. Today our four brands — SSI, NEXITONE, CORVELL and ORION — represent a complete ecosystem of tile adhesives, grouts and waterproofing solutions for every project type and budget.

GROWTH MILESTONES

Company Founded

2023

Established at HSIIDC, Panipat. Production begins with SSI brand.

ISI Certification

2024

Achieved ISI 9001:2015 — quality standards confirmed from day one.

First 100 Clients

2024

Scaled to 100+ builders across North India within 9 months.

NEXITONE Launch

2024

Launched NEXITONE — next-generation adhesives for premium projects.

CORVELL & ORION

2024

Expanded with CORVELL (True Bond) and ORION (Industrial Epoxy).

Pan-India Network

2024

Supply chain extended to all 28 Indian states and territories.

5,000+ Clients

2025

Milestone: 5,000+ clients across residential & commercial segments.

Export Quality

2025

Products achieve export-grade ratings. International expansion underway.

MANUFACTURING EXCELLENCE & QUALITY ASSURANCE

State-of-the-Art Plant

Modern facility at HSIIDC, Panipat with high-capacity production lines.

Raw Material Control

Premium materials from certified suppliers with full batch traceability.

In-House Testing Lab

Every batch tested for bond strength, open time and chemical resistance.

Zero Compromise Policy

Strict QC — every 20 kg bag meets ISI and MSME specifications.

QUALITY ASSURANCE PROCESS

1

Raw Material Inspection

Incoming materials tested for purity and chemical composition.

2

Batch Production

Precision dosing with automated plant and real-time monitoring.

3

In-House Lab Testing

Bond strength, open time and water resistance per batch.

4

BIS/ISI Verification

Products verified against BIS and ISI before release.

5

Packaging & Dispatch

Sealed 20 kg bags with batch tracking via certified logistics.

Location: Panipat, Haryana

Facility: HSIIDC Industrial Area

Founded: 2023

Certification: ISI 9001:2015

Pack Sizes: 1 / 5 / 20 kg

Supply: Pan-India

Why Choose Shiv Shakti Industries

Our Advantages · Application Areas · Technical Support · Nationwide Reach

Page 4 / 11

OUR KEY ADVANTAGES

ISI 9001:2015 Certified

Bureau of Indian Standards certification ensuring quality, consistency and safety for every application.



BIS & EN 12004 Compliant

Meets both Indian MSME and European EN 12004 international standards — export-confidence built in.



In-House Testing Lab

Dedicated quality laboratory testing every batch for bond strength, open time and chemical resistance.



Low VOC Formulation

Eco-conscious formula for healthier indoor air quality and sustainable construction practices.



Pan-India Distribution

Reliable supply chain covering all 28 states and Union Territories — timely delivery anywhere.



500+ Happy Clients

Trusted by builders, contractors, architects and developers across residential and commercial sectors.



Expert Technical Support

Dedicated technical team providing on-site support, training and troubleshooting for all products.



Competitive Pricing

Premium quality at Indian prices — genuine value without compromising performance or reliability.



Custom Solutions

Capability to develop specifications for large projects, government contracts and export requirements.



PRODUCT APPLICATION AREAS

■ Residential Flooring

Large format vitrified, ceramic and mosaic tile fixing.

■ Commercial Spaces

Shopping malls, offices, hotels and public buildings.

■ Swimming Pools

Waterproof epoxy grout and adhesive systems.

■ Bathrooms & Wet Rooms

Water-resistant adhesives and anti-mould grouts.

■ Heated Floor Systems

Thermally stable flexible adhesives for underfloor heating.

■ Industrial Facilities

Chemical-resistant epoxy for factories and food plants.

■ Hospitals & Sterile

Hygienic stain-resistant grouting for medical facilities.

■ Facade & Overlaying

Flexibilised adhesives for re-tiling and external cladding.

BECOME A DISTRIBUTOR / ORDER TODAY

Min. Order

200 TO 500 Bag (20 kg)

Delivery

Pan-India Dispatch

Phone

+91 87088 20660

WhatsApp

+91 9671100593

Website

www.shaktibuildtech.com

CERTIFIED:

ISI 9001:2015

MSME Compliant

Low VOC

EN 12004

Soon-In-House Lab

Pan-India

OUR CLIENTS & REACH

500+

Happy Clients

Builders, contractors & architects

28

States Covered

Pan-India supply chain network

100%

ISI Certified

Every product meets BIS standards

4

Pro Brands

SSI · NEXITONE · CORVELL · ORION



SSI — The Bond Professionals Trust

Flagship polymer tile adhesives & grout | BIS Compliant | ISI Certified | Export Quality | 5 Products

SSI

Founded 2023 · 5 Product Lines · 20 kg Standard Pack · Export Quality · Residential, Commercial & Wet Areas



SSI EVA-C1

Ultra Premium

SSI-01

Floor & Wall

High-performance polymer-based floor & wall adhesive for large vitrified tiles, luxury marble and export-grade projects.

Ultra High Bond

Polymer Based

Export Quality

Large Format

✓ BIS / ISI Compliant

CODE
SSI-01

COVERAGE
4–5 kg/m²

PACK
20 kg



SSI SILVA BIO

Commercial Grade

SSI-02

Commercial

Reliable floor & wall adhesive for commercial spaces with heavy foot traffic. Fast setting, highly flexibilised.

Heavy Duty

Fast Setting

Highly Flexibilised

Commercial

✓ BIS / ISI Compliant

CODE
SSI-02

COVERAGE
4–5 kg/m²

PACK
20 kg



SSI ULTRA Premium

Premium Wet Area

SSI-03

Wet Areas

Premium polymer adhesive for wet environments — pools, bathrooms and wet rooms. Rapid setting with high water resistance.

Water Resistant

Rapid Setting

Indoor & Outdoor


Wet Areas

✓ BIS / ISI Compliant

CODE
SSI-03

COVERAGE
3–4 kg/m²

PACK
20 kg



SSI Elastica Gel S1

Heat Resistant

SSI-04

Heated Floors

Engineered for underfloor and heated flooring systems. Excellent thermal stability, accommodates tile expansion.

Heat Stable

S1 Flex

Long Lasting

Thermal Floors

✓ BIS / ISI Compliant

CODE
SSI-04

COVERAGE
3–4 kg/m²

PACK
20 kg

SSI RANGE — TECHNICAL SPECIFICATIONS

Product	Code	Type	Standard	Set Time	Open Time	Temp Range	Substrate
SSI EVA-C1	SSI-01	C1 Polymer	BIS/ISI	24hr	20 min	5-35C	All Tile Types
SSI SILVA BIO	SSI-02	C1 Fast Set	BIS/ISI	24hr	15 min	5-35C	Ceramic/Vitrified
SSI ULTRA Prem.	SSI-03	C2 W/R	EN 12004	24hr	20 min	5-40C	Pools/Wet Areas
SSI Elastica S1	SSI-04	S1 Flex	EN 12004	24hr	25 min	5-45C	Heated Floors

NEXITONE — Next-Level Tile Bonding

Advanced adhesives for ceramic, vitrified & mosaic | Gold · Platinum · Silver · Diamond | 4 Products

Page 6 / 11

NEXITONE

4-Tier Series · Rapid & Quick Setting · All Surface Types · Indoor & Outdoor · Export Grade



Nexitone Gold

Gold Series

NXT-01

All Tiles

Rapid setting adhesive for ceramic, vitrified & mosaic tiles. Suitable for overlaying. Indoor and outdoor use.

Rapid Setting

Quick Hardening

Highly Flexibilised

Overlay OK

✓ BIS / ISI Compliant

CODE
NXT-01

COVERAGE
4–5 kg/m²

PACK
20 kg



Nexitone Platinum

Platinum Series

NXT-02

Vitrified

Platinum-grade adhesive for vitrified and mosaic tiles. Internal & external. Quick jointing for faster completion.

Excellent Bonding

Quick Jointing

Easy Workability

Int & Ext

✓ BIS / ISI Compliant

CODE
NXT-02

COVERAGE
4–5 kg/m²

PACK
20 kg



Nexitone Silver

Silver Series

NXT-03

All Surfaces

High-quality rapid setting silver-series adhesive. Highly flexibilised. Suitable for overlaying existing tiles.

Rapid Setting

For Overlaying

Indoor & Outdoor

High Flex

✓ BIS / ISI Compliant

CODE
NXT-03

COVERAGE
4–5 kg/m²

PACK
20 kg



Nexitone Diamond

Diamond Series

NXT-04

All Tiles

Top-tier diamond-grade adhesive. Premium quick-hardening for all tile types. Available in 25 kg for large projects.

Premium Grade

Quick Hardening

Highly Flexibilised

25 kg Pack

✓ BIS / ISI Compliant

CODE
NXT-04

COVERAGE
3–4 kg/m²

PACK
20 kg

NEXITONE SERIES — COMPARISON & SELECTION GUIDE

Series	Code	Setting	Coverage	Pack	Best For
Gold	NXT-01	Rapid	4-5 kg/m2	20 kg	General Ceramic, Vitrified, Mosaic, Overlaying
Platinum	NXT-02	Quick	4-5 kg/m2	20 kg	Vitrified & Mosaic — Internal & External
Silver	NXT-03	Rapid	4-5 kg/m2	20 kg	Overlaying Existing Tiles — All Surface Types
Diamond	NXT-04	Quick	3-4 kg/m2	20kg	Large Format Premium — Heavy Vitrified Tiles



CORVELL — Advanced Bonding Technology

True Bond Technology · Interior Floor & Wall · Silver · Platinum · Diamond · Ceramica Grout | 4 Products

Page 7 / 11

CORVELL

True Bond Technology · Floor & Wall Interior · Thermal Stability · 4 Product Lines



Corvell Silver

Silver

CVL-01

Int Floor/Wall

True Bond Technology for interior floor and wall tiles. Proven reliable adhesion across ceramic and vitrified tiles.

True Bond

Floor & Wall

Bond Forever

Interior Grade

✓ BIS / ISI Compliant

CODE
CVL-01

COVERAGE
4–5 kg/m²

PACK
20 kg



Corvell Platinum

Platinum

CVL-02

Int Floor/Wall

Platinum grade interior adhesive with superior bonding strength. Easy professional setting, excellent durability.

Strong Hold

Easy Setting

Durable

Superior Bond

✓ BIS / ISI Compliant

CODE
CVL-02

COVERAGE
4 kg/m²

PACK
20 kg



Corvell Diamond

Diamond

CVL-03

Interior Premium

Highest performance in the Corvell range. Fast setting with thermal stability for demanding interior applications.

Diamond Grade

Fast Setting

Thermal Stable

Max Performance

✓ BIS / ISI Compliant

CODE
CVL-03

COVERAGE
3–4 kg/m²

PACK
20 kg



Corvell Gold

Gold GVD-192

CVL-04

Grouting

Pore-safe Ceramica grout with exceptional stain and chemical resistance. Easy clean. Joints 2–10 mm.

Stain Resistant

Chemical Resistant

Pore Safe

2–10mm Joints

✓ BIS / ISI Compliant

CODE
CVL-04

COVERAGE
Varies

PACK
20 kg

CORVELL RANGE — COVERAGE RATES & APPLICATION GUIDE

Corvell Silver (CVL-01)		4–5 kg/m ²	
Corvell Platinum (CVL-02)		4 kg/m ²	
Corvell Diamond (CVL-03)		3–4 kg/m ²	
Corvell Grout (CVL-04)		Varies	

1 Prepare
Clean dry surface.

2 Mix
Powder+water 4.2:1.

3 Spread
Notched trowel 45°.

4 Set Tile
Firm press + twist.

5 Grout
After 24h cure.



ORION — Industrial Strength Solutions

Professional epoxy systems & grouts | Pools · Showers · Hydrotherapy · Industrial | 3 Products

ORION

Industrial Grade · Two-Part Epoxy · Pool & Hydrotherapy Rated · Chemical Resistant · Eco Friendly



Orion Epoxy Resin, AdMIXTURE & Hardener

Epoxy System

ORN-01

Industrial

Two-part epoxy: Part A Resin + Part B Hardener. High bond strength with polymer additives for chemical environments.

High Bond Strength

Polymer Additives

Chemical Resistant

2-Part

✓ BIS / ISI Compliant

CODE
ORN-01

COVERAGE
Varies

PACK
1 kg kit



Orion Epoxy Grout

Advance Protection

ORN-02

Pool & Shower

Advanced epoxy grout for pools, showers, wall & floor tiles and hydrotherapy pools. Eco-friendly, No.1 grade.

Advance Protection

Eco Friendly

No.1 Grade

Pool Rated

✓ BIS / ISI Compliant

CODE
ORN-02

COVERAGE
Varies

PACK
1 kg / 5 kg



Tile Grout

Premium Grout

GRT-03

Int & Ext

Premium interior & exterior grout for high-traffic and hygienic sterile environments such as hospitals.

Stain Resistant

Hygienic Sterile

High Traffic

Easy Clean

✓ BIS / ISI Compliant

CODE
GRT-03

COVERAGE
Varies

PACK
1 kg / 5 kg

ORION RANGE — PRODUCT COMPARISON & USE CASES

Product	Code	System	Environment	Pack	Ideal Use Case
Epoxy Resin & Hardener	ORN-01	2-Part Epoxy	Industrial/Chemical	1 kg kit	Factories, Labs, Chemical Floors
Epoxy Grout	ORN-02	Epoxy Grout	Wet/Pool/Hydro	1/5 kg	Pools, Showers, Hydrotherapy
Tile Grout	ORN-03	Prem. Grout	Int & Ext / Sterile	1/5 kg	Hospitals, Food Plants, High Traffic

All ORION products: Eco-Friendly · Low VOC · No.1 Grade Epoxy · Chemical & Stain Resistant

STEP 1 MIX
Mix the Part A & Part B components thoroughly to achieve a smooth, uniform paste.

STEP 2 APPLY
Apply the grout using a rubber float, pressing firmly into the joints and removing excess.

STRONG BOND. PERFECT FINISH.

ORION EPOXY GROUT – FOR DURABLE, BEAUTIFUL SPACES

High Performance Epoxy Grout for Stronger Joints, Stain Resistance & Long Lasting Beauty.

- STRONG BOND**
Ensures high strength and durability.
- WATER & STAIN RESISTANT**
Resists water, stains, chemicals and dirt.
- SMOOTH FINISH**
Delivers a smooth, attractive and professional finish.
- LONG LASTING**
Built to last for years without cracks or shrinkage.

HIGH STRENGTH
Superior bond & durability

CHEMICAL RESISTANT
Resists chemicals and harsh conditions

WIDE APPLICATION
Suitable for tiles, stones, mosaics & more

EASY TO USE
Smooth application and easy cleaning

ECO FRIENDLY
Low VOC, safe for environment

ALL 16 PRODUCTS — FULL REFERENCE TABLE

Code	Product Name	Brand	Type	Application	Coverage	Pack	Standard	Grade
SSI-01	SSI EVA-C1	SSI	C1 Polymer	Floor & Wall	4-5 kg/m2	20 kg	BIS/ISI	Ultra Premium
SSI-02	SSI SILVA BIO	SSI	C1 Fast Set	Commercial F&W	4-5 kg/m2	20 kg	BIS/ISI	Commercial
SSI-03	SSI ULTRA Premium	SSI	C2 W/R	Wet Areas / Pools	3-4 kg/m2	20 kg	EN 12004	Premium
SSI-04	SSI Elastica Gel S1	SSI	S1 Flex	Heated Floors	3-4 kg/m2	20 kg	EN 12004	Heat Resist.
SSI-05	SSI Tile Grout	SSI	CG2 Grout	Grouting	Varies	1 kg	BIS	Prem. Grout
NXT-01	Nexitone Gold	NEXITONE	C1 Rapid	All Tiles	4-5 kg/m2	20 kg	BIS/ISI	Gold Series
NXT-02	Nexitone Platinum	NEXITONE	C1 Quick	Vitrified/Mosaic	4-5 kg/m2	20 kg	BIS/ISI	Platinum
NXT-03	Nexitone Silver	NEXITONE	C1 Rapid	All/Overlaying	4-5 kg/m2	20 kg	BIS/ISI	Silver
NXT-04	Nexitone Diamond	NEXITONE	C1 Premium	All Tile Types	3-4 kg/m2	20 kg	BIS/ISI	Diamond
CVL-01	Corvell Silver	CORVELL	True Bond	Int Floor & Wall	4-5 kg/m2	20 kg	BIS/ISI	Silver
CVL-03	Corvell Platinum	CORVELL	Platinum	ext Floor & Wall	4 kg/m2	20 kg	BIS/ISI	Platinum
CVL-04	Corvell Diamond	CORVELL	Diamond	Interior Premium	3-4 kg/m2	20 kg	BIS/ISI	Diamond
CVL-02	Corvell Gold	CORVELL	CG2 Ceramic	wall&flooe	Varies	20 kg	BIS/ISI	Ceramica
ORN-01	Orion Epoxy Resin & Hdnr	ORION	2-Part Epoxy	Industrial	Varies	1 kg kit	BIS/ISI	Epoxy Sys.
ORN-02	Orion Epoxy Grout	ORION	Epoxy Grout	Pool & Shower	Varies	1/5 kg	BIS/ISI	Adv. Prot.
ORN-03	Orion Tile Grout	ORION	Prem. Grout	Int & Ext	Varies	1/5 kg	BIS/ISI	Prem. Grout

COVERAGE & PACK SIZE — QUICK REFERENCE

Product	Code	Coverage	Pack	Product	Code	Coverage	Pack
SSI EVA-C1	SSI-01	4-5 kg/m2	20 kg	Nexitone Gold	NXT-01	4-5 kg/m2	20 kg
SSI SILVA BIO	SSI-02	4-5 kg/m2	20 kg	Nexitone Platinum	NXT-02	4-5 kg/m2	20 kg
SSI ULTRA Prem.	SSI-03	3-4 kg/m2	20 kg	Nexitone Silver	NXT-03	4-5 kg/m2	20 kg
SSI Elastica S1	SSI-04	3-4 kg/m2	20 kg	Nexitone Diamond	NXT-04	3-4 kg/m2	20/25 kg
SSI Tile Grout	SSI-05	Varies	1 kg	Corvell Silver	CVL-01	4-5 kg/m2	20 kg
Corvell Diamond	CVL-03	3-4 kg/m2	20 kg	Corvell Platinum	CVL-02	4 kg/m2	20 kg
Corvell Gold	CVL-04	Varies	5 kg	Orion Epoxy Resin	ORN-01	Varies	1 kg kit
Orion Epoxy Grout	ORN-02	Varies	1/5 kg	Orion Tile Grout	ORN-03	Varies	1/5 kg

PORTFOLIO SUMMARY — 16 PRODUCTS — 4 BRANDS

SSI Brand

5 Products

NEXITONE

4 Products

CORVELL

4 Products

ORION

3 Products

ORDER NOW / BECOME A DISTRIBUTOR

+91 87088 20660 | +91 96711 00593 | info@shivshaktiindustries.com

HSIIDC Industrial Area, Samalkha, Panipat, Haryana - 132101 | Mon-Sat 9AM-6PM

COMPLETE APPLICATION PROCESS — STEP BY STEP

Surface Preparation

Ensure surface is clean, dry, dust-free and structurally sound. Remove loose particles, paint, oil or grease. Fill cracks and level uneven areas. Allow new concrete to cure at least 28 days before tiling.

STEP 1

Mixing the Adhesive

Add powder to clean water at 4.2:1 ratio by weight. Mix with a slow-speed drill until smooth and lump-free. Allow to rest (slake) for 5 minutes then re-mix briefly before use.

STEP 2

Applying the Adhesive

Spread adhesive with a notched trowel at 45°. Use the flat side first to key the substrate, then the notched side to create ridges. Work in 1m² sections to prevent skin-over.

STEP 3

Setting the Tile

Press each tile firmly with a slight twisting action (min. 80% coverage, 95% for wet areas). Check alignment and levelness. Use spacers for consistent grout joints throughout.

STEP 4



STRONG BOND. PERFECT FINISH.

HOW TO USE SSI TILE ADHESIVE & EPOXY GROUT

A simple 5-step process for stronger bonds and beautiful spaces.

01		SURFACE PREPARATION Ensure surface is clean, dry, dust-free and structurally sound. Remove loose particles, paint, oil or grease. Fill cracks and level uneven areas. Allow new concrete to cure at least 28 days before tiling.	
02		MIXING THE ADHESIVE Add powder to clean water at 4.2:1 ratio by weight. Mix with a slow-speed drill until smooth and lump-free. Allow to rest (slake) for 5 minutes then re-mix briefly before use.	
03		APPLYING THE ADHESIVE Spread adhesive with a notched trowel at 45°. Use the flat side first to key the substrate, then the notched side to create ridges. Work in 1m ² sections to prevent skin-over.	
04		SETTING THE TILE Press each tile firmly with a slight twisting action (min. 80% coverage, 95% for wet areas). Check alignment and levelness. Use spacers for consistent grout joints throughout.	
05		GROUTING After minimum 24-hour cure, apply grout using a rubber float at 45° to joints. Remove excess within 15-20 minutes using a damp sponge. Avoid foot traffic for 24 hours after grouting.	



HIGH STRENGTH
Superior bond & durability



WATER & CHEMICAL RESISTANT
For long lasting performance



FOR ALL TILE TYPES
Ceramic, vitrified, porcelain & more



INTERIOR & EXTERIOR
Suitable for walls, floors & wet areas



EASY TO USE
Smooth application & excellent workability



STRONG BOND. PERFECT FINISH.
TRUST SSI.

SHIV SHAKTI INDUSTRIES

Strong Bond · Lasting Trust
India's Trusted Tile Adhesive Manufacturer



GET IN TOUCH WITH US

Address

HSI IDC Industrial Area, Samalkha, Panipat, Haryana – 132101

WhatsApp

+91 87088 20660 | +91 96711 00593

Hours

Monday – Saturday: 9:00 AM – 6:00 PM

Phone

+91 87088 20660

Email

info@shivshaktiindustries.com

Factory

HSI IDC Industrial Area, Samalkha, Panipat (HR)

OUR 4 PROFESSIONAL BRANDS

SSI

The Bond Professionals Trust

NEXITONE

Next-Level Tile Bonding

CORVELL

Advanced Bonding Technology

ORION

Industrial Strength Solutions



STRONG BOND. PERFECT FINISH.

ORION EPOXY GROUT – FOR DURABLE, BEAUTIFUL SPACES

High Performance Epoxy Grout for Stronger Joints,
Stain Resistance & Long Lasting Beauty.



STRONG BOND
Ensures high strength and durability.



WATER & STAIN RESISTANT
Resists water, stains, chemicals and dirt.



SMOOTH FINISH
Delivers a smooth, attractive and professional finish.



LONG LASTING
Built to last for years without cracks or shrinkage.

COMPLETE PRODUCT INDEX



ORION EPOXY GROUT (Part A)

Resin based component that provides strength, bond and durability.
Net Weight: 5kg



ORION EPOXY GROUT (Part B)

Hardener component that ensures proper curing and performance.
Net Weight: 1kg



ORION EPOXY GROUT (Mixed)

Combines strength, aesthetics and long-lasting protection.
Net Weight: 6kg (Approx.)



ORION EPOXY GROUT (Bag Pack)

High quality grout for large area applications with consistent performance.
Net Weight: 1kg, 5kg, 20kg



WHAT IS ORION EPOXY GROUT?

A high performance epoxy based grout that gives a strong bond, stain resistance, chemical resistance and a perfect finish for all types of tiles and stones.

KEY FEATURES

- ✓ High Strength & Durability
- ✓ Water, Stain & Chemical Resistant
- ✓ Smooth & Non-Shrink Finish
- ✓ Suitable for Interior & Exterior
- ✓ Easy to Clean & Maintain
- ✓ Wide Range of Applications

WHERE TO USE



Interior & Exterior
Residential & Commercial
All Types of Tiles, Stones & Mosaic

HOW TO APPLY (STEP BY STEP)


- 1. CLEAN THE SURFACE**
Ensure the tiles and joints are oil or loose particles.
- 2. MIX THE COMPONENTS**
Mix Part A (Resin) and Part B (Hardener) thoroughly as per the recommended ratio until you get a uniform paste.
- 3. APPLY THE GROUT**
Use a rubber float to apply the grout diagonally across the joints, filling them completely.
- 4. REMOVE EXCESS**
Remove excess grout using a damp sponge before it starts to harden.
- 5. FINAL FINISH**
Once set, wipe the surface with a clean, dry cloth for a smooth and shiny finish.

OUR COMPLETE PRODUCT RANGE



PERFECT FOR EVERY PROJECT

From homes to commercial spaces, our tile adhesive solutions are designed to deliver strength, beauty and long-lasting results.



HIGH STRENGTH
Superior bond & durability



CHEMICAL RESISTANT
Resists chemicals and harsh conditions



WIDE APPLICATION
Suitable for tiles, stones, mosaics & more



EASY TO USE
Smooth application and easy cleaning



ECO FRIENDLY
Low VOC, safe for environment

CHOOSE **ORION** EPOXY GROUT FOR STRONGER JOINTS, BEAUTIFUL SPACES & A PERFECT FINISH.

STRONG BOND. PERFECT FINISH. TRUST SSI.